

UNITA' CONDENSANTRICI AD ARIA A VALVOLA

 Embraco aspera



EMBRACO R134a MHBP

220/240v 1Ph 50Hz

Modello	HP	Motore	Ricevitore Lt.	Connessioni		Capacità in W TC = + 54,4°C					Dimensioni mm.			Peso Kg.
				IN	OUT	- 15	- 10	- 5	0	+ 5	L	P	A	
UEMT6144Z-C2	1/5	CSIR	0,6	3/8"	1/4"	221	280	349	431	523	431	306	226	17
UEMT6160Z-C2	1/4	CSIR	1,1	3/8"	1/4"	297	373	465	571	692	435	306	254	18
UNEK6187Z-C2	1/3	CSIR	1,1	3/8"	1/4"	359	457	574	711	870	467	339	296	21
UNEK6214Z-C2	1/2	CSIR	1,1	3/8"	1/4"	584	750	935	1139	1368	467	339	296	24
UNJ6220Z-C2	3/4	CSR	2,3	1/2"	3/8"	625	775	942	1135	2193	465	340	296	28

EMBRACO R404a / R507 / R452a MHBP

220/240v 1Ph 50Hz

Modello	HP	Motore	Ricevitore Lt.	Connessioni		Capacità in W TC = + 54,4°C					Dimensioni mm.			Peso Kg.
				IN	OUT	- 15	- 10	- 5	0	+ 5	L	P	A	
UEMT6144GK-C2	1/5	CSIR	0,6	3/8"	1/4"	300	363	438	519	603	431	306	226	18
UEMT6165GK-C2	1/4	CSIR	1,1	3/8"	1/4"	395	477	583	697	799	435	306	254	20
UNEK6181GK-C2	1/3	CSIR	1,1	3/8"	1/4"	470	585	715	860	1020	467	339	296	21
UNEK6210GK-C2	3/8	CSIR	1,1	3/8"	1/4"	670	765	886	1032	1228	467	339	296	23
UNEK6213GK-C2	1/2	CSIR	1,1	3/8"	1/4"	802	966	1130	1292	1439	467	339	296	24
UNEK6217GK-C2	5/8	CSR	2,3	3/8"	3/8"	960	1180	1406	1640	1880	470	395	324	26

EMBRACO R404a / R507 / R452a LBP

220/240v 1Ph 50Hz

Modello	HP	Motore	Ricevitore Lt.	Connessioni		Capacità in W TC = + 54,4°C					Dimensioni mm.			Peso Kg.
				IN	OUT	- 30	- 25	- 20	- 15	- 10	L	P	A	
UEMT2125GK-C2	1/3	CSIR	1,1	3/8"	1/4"	231	325	419	537	655	460	325	265	20
UNEK2134GK-C2	1/2	CSIR	1,1	3/8"	1/4"	337	456	593	733	884	467	339	296	21
UNEK2150GK-C2	5/8	CSIR	1,1	3/8"	1/4"	474	569	683	817	969	467	339	296	26
UNEK2168GK-02	3/4	CSR	1,2	3/8"	1/4"	484	643	825	994	1153	467	340	296	30

Nota : le rese sono riferite a temperatura ambiente +32°C

L'unità condensatrice si compone di : basamento, compressore, condensatore, ventola, ricevitore e rubinetti.



SuperSamaStore – C.so promessi sposi 23-B – 23900 Lecco