



# TIEMME

## RACCORDI A PRESSARE PER GAS PRESS FITTINGS FOR GAS

### Serie 2650

### Raccordi a pressione per tubo multistrato. Press fittings for multilayer pipes.

I raccordi a pressione Serie 2650 sono prodotti per essere utilizzati nella distribuzione di gas naturali e si adattano ad ogni tipo di impianto idraulico domestico e commerciale, applicazioni industriali ed agricole, impianti di riscaldamento ed igienico sanitari, olii vari, prodotti petroliferi e generalmente con ogni fluido non corrosivo. Mediante questi raccordi si realizzano giunzioni di tipo irreversibile e quindi sono posizionabili sotto traccia come previsto dalle normative.

The press fittings Serie 2650 are manufactured can be properly used for gas distribution and are suitable for domestic and commercial plumbing, industrial and agricultural application, heating and sanitary system, oils and generally with every non aggressive fluid. Connection made with these fitting are irreversible and therefore may be placed under floor as required by regulations.



Per la gamma completa vedere il catalogo / For complete range see catalogue



Certificazioni / Certifications



#### Caratteristiche Tecniche

Temperatura max di esercizio : 95°C  
Temperatura min di esercizio : -20°C (\*)  
Pressione max di esercizio : 10 bar (relativo al tubo multistrato)  
Filettature : femmina UNI ISO 228  
maschio UNI ISO 7/1 conico

#### Technical Features

Maximum temperature : 95°C  
Minimum temperature : -20°C (\*)  
Maximum operating pressure : 10 bar (referred to multilayer pipe)  
Threads : female UNI ISO 228  
male UNI ISO 7/1 conical

#### Descrizione

Corpo  
O-ring  
Bussola  
Ghiera isolante

#### Materiale

Ottone CW617N - EN12165  
Ottone CW617N - EN12164  
Gomma nitrilica (HNBR) gialla  
Acciaio Inox AISI 304  
Nylon giallo

#### Trattamento

-  
-  
-  
-

#### Description

Body  
O-ring  
Bushing  
Plasting ring

#### Material

CW617N - EN12165 brass  
CW617N - EN12164 brass  
Nitrile rubber (HNBR) yellow  
Stainless steel AISI 304  
Yellow nylon

#### Treatment

-  
-  
-  
-

(\*) purché il fluido rimanga in fase liquida / provided that the fluid remains in the liquid phase

#### Istruzioni per il corretto montaggio :

Il taglio del tubo deve essere eseguito con attrezzature idonee ad ottenere un taglio senza bave e perfettamente perpendicolare all'asse del tubo. L'estremità tagliata deve inoltre essere sbavata utilizzando l'utensile calibratore/sbavatore Art. 1498. Calzare il tubo sul portagomma e eseguire la pressatura del raccordo utilizzando la pressatrice (Art. 1685-1686) e la pinza con profilo TH personalizzata "TM" della misura idonea per il tubo in uso.

#### Instruction for the correct assembly :

The pipe cut shall be done with appropriate toolings in order to obtain a precise and perpendicular cut without any trimming. The pipe end shall be cleaned using the deburring tool Art. 1498. Fit the pipe on the fitting press it using the crimping machine (Art. 1685-1686) and the pressing tongs "TH" profile personalized "TM" model for the specific size of the pipe in use.



TIEMME Raccorderie S.p.A.  
Via Cavallera 6/A (Loc. Barco) - 25045 Castegnato (Bs) - Italy  
Tel +39 030 2142211 R.A. - Fax +39 030 2142206  
info@tiemme.com - www.tiemme.com

©TIEMME Raccorderie S.p.A. 2650 Rev. D 05-13



TIEMME Raccorderie S.p.A. si riserva di apportare modifiche in qualsiasi momento senza preavviso.  
TIEMME Raccorderie S.p.A. reserves the right to modify contents many time without prior advise.  
E' vietata qualsiasi forma di riproduzione, se non autorizzata.  
Is forbidden any reproduction unless under TIEMME authorization

