

UNITA' CONDENSANTRICI AD ARIA A VALVOLA

Embraco



EMBRACO R134a MHBP

220/240v 1Ph 50Hz

Modello	HP	Motore	Ricev. Lt.	Conessioni		Capacità in W TC = + 54,4°C					Dimens. mm.			Peso Kg.	EURO
				IN	OUT	- 15	- 10	- 5	0	+ 5	L	P	A		
UEMT6144Z-2	1/5	CSIR	0,6	3/8"	1/4"	221	280	349	431	523	431	306	226	17	212,70
UEMT6160Z-2	1/4	CSIR	1,1	3/8"	1/4"	297	373	465	571	692	435	306	254	18	225,00
UNEK6187Z-2	1/3	CSIR	1,1	3/8"	1/4"	359	457	574	711	870	467	339	296	21	228,03
UNEK6214Z-2	1/2	CSIR	1,1	3/8"	1/4"	584	750	935	1139	1368	467	339	296	24	255,74
UNJ6220Z-2	3/4	CSIR	2,3	1/2"	3/8"	1011	1259	1537	1849	2193	481	409	324	28	391,80
UNJ6226Z-2	1	CSR	2,3	5/8"	3/8"	1372	1686	2035	2419	2814	481	409	324	32	403,28

EMBRACO R404a / R507 / R452a MHBP

220/240v 1Ph 50Hz

Modello	HP	Motore	Ricev. Lt.	Conessioni		Capacità in W TC = + 54,4°C					Dimens. mm.			Peso Kg.	EURO
				IN	OUT	- 15	- 10	- 5	0	+ 5	L	P	A		
UEMT6144GK-2	1/5	CSIR	0,6	3/8"	1/4"	300	363	438	519	603	431	306	226	18	212,70
UEMT6165GK-2	1/4	CSIR	1,1	3/8"	1/4"	395	477	583	697	799	435	306	254	20	220,41
UNEK6181GK-2	1/3	CSIR	1,1	3/8"	1/4"	470	585	715	860	1020	467	339	296	21	231,56
UNEK6210GK-2	3/8	CSIR	1,1	3/8"	1/4"	670	765	886	1032	1228	467	339	296	23	233,61
UNEK6213GK-2	1/2	CSIR	1,1	3/8"	1/4"	802	966	1130	1292	1439	467	339	296	24	240,98
UNEK6217GK-2	5/8	CSR	2,3	3/8"	3/8"	960	1180	1406	1640	1880	470	395	324	26	304,92
UNT6222GK-2	1-	CSR	2,3	1/2"	3/8"	1122	1389	1679	1989	2316	518	395	324	28	326,40
UNT6226GK-2	1	CSR	2,3	1/2"	3/8"	1568	1878	2198	2526	2864	500	405	390	32	412,00
UNJ9232GK-2	1,2	CSR	3,9	5/8"	1/2"	1764	2124	2512	2898	3294	600	440	379	38	463,30
UNJ9238GK-2	1,5	CSR	3,9	5/8"	1/2"	2147	2560	3157	3434	3895	461	787	331	44	489,90

EMBRACO R404a / R507 / R452a LBP

220/240v 1Ph 50Hz

Modello	HP	Motore	Ricev. Lt.	Conessioni		Capacità in W TC = + 54,4°C					Dimens. mm.			Peso Kg.	EURO
				IN	OUT	- 30	- 25	- 20	- 15	- 10	L	P	A		
UEMT2125GK-2	1/3	CSIR	1,1	3/8"	1/4"	231	325	419	537	655	460	325	265	20	225,00
UNEK2134GK-2	1/2	CSIR	1,1	3/8"	1/4"	337	456	593	733	884	467	339	296	21	240,16
UNEK2150GK-2	5/8	CSIR	1,1	3/8"	1/4"	474	569	683	817	969	467	339	296	26	271,80
UNEK2168GK-2	3/4	CSR	1,2	3/8"	1/4"	484	643	825	994	1153	467	340	296	30	287,70

Nota : le rese sono riferite a temperatura ambiente +32°C

L'unità condensatrice si compone di : basamento, compressore, condensatore, ventola, ricevitore e rubinetti.