

COMPRESSOR DEFINITION

Designation	EM T2121GK
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	912CA67

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure R404A		
4.1 Evaporating temperature range	-40°C to -10°C	(-40°F to 14°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	25.7	[kgf/cm ²] (365 psig)	/ °C - °F
9.2 Peak (gauge)	28.7	[kgf/cm ²] (408 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/3	[hp]
2 Displacement	5.19	[cm ³] (0.317 cu.in)
2.1 Bore [mm]	21.000	
2.2 Stroke [mm]	15.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	7.8	[kg] (17.20 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRP-34	
3 Start capacitor	43-53(330)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0827/G6	
6 Start winding resistance	[Ω at 25°C (77°F)] +/- 8%	
7 Run winding resistance	[Ω at 25°C (77°F)] +/- 8%	
8 LRA - Locked rotor amperage (50 Hz)	8.50	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			EN12900LBP_HH Fan		Evaporating temperature (Condensing temperature		-35°C (-31°F) 40°C (104°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
594	150	174	155	1.19	4.37	3.82	0.96	1.12

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			EN12900HH Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	493	124	145	135	1.14	3.41	3.65	0.92	1.07
-35	(-31)	649	164	190	152	1.18	4.52	4.27	1.08	1.25
-30	(-22)	835	210	245	170	1.23	5.83	4.91	1.24	1.44
-25	(-13)	1055	266	309	189	1.28	7.40	5.59	1.41	1.64
-20	(- 4)	1317	332	386	208	1.34	9.27	6.32	1.59	1.85
-15	(+ 5)	1624	409	476	228	1.40	11.51	7.14	1.80	2.09
-10	(+14)	1983	500	581	246	1.47	14.17	8.05	2.03	2.36

TEST CONDITIONS: @220V50Hz			EN12900HH Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	411	104	120	140	1.14	3.20	2.95	0.74	0.86
-35	(-31)	542	137	159	158	1.19	4.24	3.42	0.86	1.00
-30	(-22)	696	175	204	179	1.25	5.46	3.89	0.98	1.14
-25	(-13)	880	222	258	201	1.31	6.94	4.37	1.10	1.28
-20	(- 4)	1098	277	322	224	1.39	8.71	4.89	1.23	1.43
-15	(+ 5)	1357	342	398	248	1.47	10.84	5.47	1.38	1.60
-10	(+14)	1661	419	487	272	1.56	13.38	6.12	1.54	1.79

TEST CONDITIONS: @220V50Hz			EN12900HH Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	334	84	98	141	1.13	3.01	2.36	0.60	0.69
-35	(-31)	444	112	130	162	1.19	4.01	2.74	0.69	0.80
-30	(-22)	572	144	167	185	1.27	5.18	3.09	0.78	0.91
-25	(-13)	722	182	212	210	1.35	6.60	3.44	0.87	1.01
-20	(- 4)	901	227	264	238	1.45	8.30	3.79	0.95	1.11
-15	(+ 5)	1114	281	327	267	1.55	10.34	4.18	1.05	1.22
-10	(+14)	1367	345	401	296	1.66	12.79	4.62	1.16	1.35

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		