

### COMPRESSOR DEFINITION

Designation	<b>NE K6210GK</b>
Nominal Voltage/Frequency	<b>220-240 V 50 Hz</b>
Engineering Number	<b>958CA51</b>

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	25.7	[kgf/cm <sup>2</sup> ] (365 psig)	/ °C - °F
9.2 Peak (gauge)	28.7	[kgf/cm <sup>2</sup> ] (408 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/2	[hp]
2 Displacement	8.77	[cm <sup>3</sup> ] (0.535 cu.in)
2.1 Bore [mm]	26.497	
2.2 Stroke [mm]	15.920	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11	[kg] (24.25 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELECTRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRP-0029	
3 Start capacitor	53-64(330)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0660/G5	
6 Start winding resistance	31.70	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	5.18	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	16.10	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - IMQ	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
4449	1121	1304	628	3.49	36.63	7.08	1.78	2.07

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2162	545	634	328	2.26	13.72	6.59	1.66	1.93
-15	(+ 5)	2627	662	770	360	2.38	16.78	7.30	1.84	2.14
-10	(+14)	3213	810	941	390	2.50	20.64	8.23	2.07	2.41
-5	(+23)	3920	988	1149	419	2.61	25.36	9.36	2.36	2.74
0	(+32)	4748	1197	1391	445	2.72	30.99	10.66	2.69	3.12
+5	(+41)	5698	1436	1670	470	2.82	37.58	12.12	3.05	3.55
+10	(+50)	6769	1706	1984	494	2.92	45.18	13.69	3.45	4.01

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	1920	484	563	350	2.31	13.45	5.48	1.38	1.61
-15	(+ 5)	2300	580	674	392	2.48	16.22	5.88	1.48	1.72
-10	(+14)	2787	702	817	432	2.64	19.78	6.46	1.63	1.89
-5	(+23)	3382	852	991	469	2.80	24.19	7.21	1.82	2.11
0	(+32)	4085	1029	1197	504	2.95	29.50	8.10	2.04	2.37
+5	(+41)	4894	1233	1434	538	3.09	35.77	9.10	2.29	2.67
+10	(+50)	5812	1465	1703	569	3.23	43.04	10.20	2.57	2.99

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	1525	384	447	365	2.36	11.99	4.18	1.05	1.22
-15	(+ 5)	1855	467	544	419	2.58	14.69	4.43	1.12	1.30
-10	(+14)	2278	574	668	470	2.79	18.18	4.84	1.22	1.42
-5	(+23)	2795	704	819	519	3.00	22.51	5.38	1.36	1.58
0	(+32)	3405	858	998	565	3.20	27.73	6.03	1.52	1.77
+5	(+41)	4109	1036	1204	609	3.40	33.90	6.76	1.70	1.98
+10	(+50)	4907	1237	1438	650	3.59	41.06	7.55	1.90	2.21

### F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		