

COMPRESSOR DEFINITION

Designation	NT 6226GK
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	923BA02

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	25.7	[kgf/cm ²] (365 psig)	/ °C - °F
9.2 Peak (gauge)	28.7	[kgf/cm ²] (408 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1+	[hp]
2 Displacement	22.37	[cm ³] (1.365 cu.in)
2.1 Bore [mm]	36.990	
2.2 Stroke [mm]	20.830	
3 Lubricant charge	450	[ml] (15.22 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	17.5	[kg] (38.58 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA403C-123	
3 Start capacitor	130-156(250)	[µF(VAC minimum)]
4 Run capacitor	20(440)	[µF(VAC minimum)]
5 Motor protection	T0828/C9	
6 Start winding resistance	8.40	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.70	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	IMQ	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			EN12900MBP Fan		Evaporating temperature (Condensing temperature		-10°C (14°F) 45°C (113°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
5978	1506	1752	980	4.78	52.62	6.10	1.54	1.79

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		EN12900 Fan			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	4643	1170	1360	764	3.83	35.28	6.07	1.53	1.78
-15	(+ 5)	5822	1467	1706	831	4.12	44.58	7.01	1.77	2.05
-10	(+14)	7222	1820	2116	898	4.42	55.78	8.04	2.03	2.36
-5	(+23)	8845	2229	2592	966	4.72	69.05	9.16	2.31	2.68
0	(+32)	10690	2694	3132	1035	5.03	84.52	10.33	2.60	3.03
+5	(+41)	12757	3215	3738	1106	5.35	102.35	11.55	2.91	3.38
+10	(+50)	15046	3792	4409	1181	5.69	122.69	12.79	3.22	3.75

TEST CONDITIONS: @220V50Hz		EN12900 Fan			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3801	958	1114	821	4.08	32.83	4.63	1.17	1.36
-15	(+ 5)	4804	1211	1408	901	4.43	41.86	5.33	1.34	1.56
-10	(+14)	5990	1509	1755	980	4.78	52.72	6.11	1.54	1.79
-5	(+23)	7359	1855	2156	1059	5.13	65.56	6.95	1.75	2.04
0	(+32)	8912	2246	2611	1138	5.49	80.54	7.83	1.97	2.29
+5	(+41)	10648	2683	3120	1218	5.86	97.81	8.74	2.20	2.56
+10	(+50)	12567	3167	3683	1300	6.23	117.52	9.65	2.43	2.83

TEST CONDITIONS: @220V50Hz		EN12900 Fan			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3072	774	900	869	4.30	31.21	3.53	0.89	1.04
-15	(+ 5)	3890	980	1140	967	4.73	39.93	4.02	1.01	1.18
-10	(+14)	4852	1223	1422	1062	5.16	50.41	4.57	1.15	1.34
-5	(+23)	5959	1502	1746	1156	5.58	62.80	5.16	1.30	1.51
0	(+32)	7210	1817	2113	1249	6.01	77.26	5.77	1.45	1.69
+5	(+41)	8606	2169	2522	1342	6.44	93.94	6.39	1.61	1.87
+10	(+50)	10146	2557	2973	1435	6.88	112.98	7.00	1.76	2.05

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Vertical		
3.2 DISCHARGE	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Vertical		
3.3 PROCESS	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		