


TEKNO CURVO | CURVED TEKNO

Ø 22mm



FORNITURA STANDARD | STANDARD SUPPLY


 Bianco RAL9010 | White RAL9010
 Finitura: lucido | Glossy finishing

Fornito con attacchi da ½" e comprensivo di valvolina di sfiato e kit di fissaggio

Supplied with ½" connections, incl. vent valve and fixing kit

TEKNO CURVO | CURVED TEKNO

Ø 22mm

Codice Code	N° tubi N° pipes	A mm	B mm	C mm	KG	LT	WAT 30°C	WAT 40°C	WAT 50°C
ASTCV F 9010 450 770	17	770	450	400	5,2	3,5	178	254	334
ASTCV F 9010 500 770	17	770	500	450	5,6	3,7	196	279	367
ASTCV F 9010 550 770	17	770	550	500	6,1	4,0	214	305	401
ASTCV F 9010 600 770	17	770	600	550	6,4	4,3	232	330	434
ASTCV F 9010 450 1200	25	1200	450	400	7,7	5,2	261	372	490
ASTCV F 9010 500 1200	25	1200	500	450	8,9	5,6	290	413	543
ASTCV F 9010 550 1200	25	1200	550	500	9,0	6,0	318	453	596
ASTCV F 9010 600 1200	25	1200	600	550	9,5	6,4	348	494	650
ASTCV F 9010 450 1500	32	1500	450	400	9,8	6,6	325	462	608
ASTCV F 9010 500 1500	32	1500	500	450	10,5	7,1	359	511	672
ASTCV F 9010 550 1500	32	1500	550	500	11,7	7,6	394	561	737
ASTCV F 9010 600 1500	32	1500	600	550	12,0	8,1	429	610	801
ASTCV F 9010 450 1800	36	1800	450	400	11,3	7,5	386	548	720
ASTCV F 9010 500 1800	36	1800	500	450	12,0	8,2	425	604	793
ASTCV F 9010 550 1800	36	1800	550	500	13,0	8,8	464	659	865
ASTCV F 9010 600 1800	36	1800	600	550	13,8	9,4	503	714	938

D=47 mm > 67 mm
 E=30 mm
 F=62 mm > 82 mm

